



WHB-TP12 Bulk Pallet Unitizer for Beverage Containers

for Beverage Containers

A significant innovation for unitizing beverage containers, the MHB-TP12 provides consistent, retained strap tension throughout the transportation cycle, resulting in improved package performance. Built with fewer parts and with features that facilitate easier maintenance and operation, the MHB-TP12 provides the lowest cost of ownership available.

Multi-level tensioning system

The MHB-TP12's innovative tensioning system equalizes the strap tension from the top and bottom to provide more accurate strap tension that stays consistent throughout the cycling process.

Specially formulated strap

Signode's 1612 Tenax polyester strapping is engineered specifically for the beverage industry to improve the overall quality of loads. Its unique composition enables larger coils of strap, resulting in fewer coil changeovers and less waste. Tenax 1612 is also fully recyclable.

MHB Sealing Modular module **Tensioning** Strapping module Heads

Easier to operate

Constructed with fewer moving parts and more durable wear parts, the MHB strapping head modules cost less to maintain than other strapping heads.

Less downtime

Separate, lightweight tensioning and sealing modules are easy to access and remove for maintenance, drastically reducing downtime. When switching to a spare module, the MHB-TP12 can be up and running in minutes.

24.831 43.281 . (630.75 mm) (1099.2 mm) 5.69" 14 48' (144 56 mm) (367.84 mm) Strap center line 14.79" (375 76 mm) 38.98" Dispenser location (989.98 mm) Door open (4517.84 mm) Maximum 113" H x 60" W Strap feed (2870 mm x 1524 mm) 120 751 (3067 mm) 4.13 (104.83 mm) Weld center line Minimum 41.74" package 22" to 26" (1060.2 mm) (564 mm to 665 mm) (914 mm PSM maximum travel 20" (502 mm) Adjustable conveyor height minimum travel 3" (76.2 mm) 5" to 20" (127 to 508 mm) – in .5" (12.7 mm) increments Maximum PSM float 4" (101.6 mm) (609.6 mm)

For more information on the MHB-TP12. call your Signode Beverage Industry Specialist at 1-800-531-1022.

Specifications

Load height

Minimum: 36" (914 mm) Maximum: 113" (2870 mm)

Load width

Minimum: 30" (762 mm) Maximum: 60" (1524 mm)

Strap requirements

1612 Tenax polyester strapping

Conveyor height

Adjustable 5-20"

Electrical

460 volts, 60Hz, 3 phase; UL Approved panels

Shipping weight

1,300 lbs to 2,100 lbs (590 kg to 953 kg) depending on the model.

Options

- Spare head
- Strap applied finger
- Light tower



Signode Packaging Systems 3650 West Lake Avenue • Glenview, Illinois 60026 1-800-531-1022 • www.signode.com