

# KLS

## Sealless Steel Strapping Head

### Simple, durable, all electric

No adjustments or settings are necessary.



### Sealless joint

The KLS forms a sealless joint, eliminating the cost of metal seals.

### Easy to operate and maintain

The KLS's modular design offers fast, easy maintenance. The sealing module and tension wheel can be removed in 5 minutes, ensuring quick changeover and minimal downtime.

**Made in the U.S.A.**

### Specifications:

For use on 1/2", 5/8" and 3/4"  
(12.7mm, 15.9mm and 19.0mm)  
Apex Plus™ and Magnus® steel  
strapping in gauges up to .031"  
(0.79mm).

Tension: Up to 1600 lbs. (7 000 N)

Electrical: 230/460 volts, 3 phase,  
60 Hz standard; 208/415 volts,  
3 phase, 50 Hz optional

Weight: 253 lbs. (114.8 kg)

**T**he KLS sealless steel strapping head is designed for 1/2", 5/8" and 3/4" (12.7mm, 15.9mm and 19.0mm) Apex Plus™ and Magnus® steel strapping in gauges up to .031" (0.79mm). This versatile strapping head is designed for medium to heavy-duty applications in a wide range of industries, including metals and lumber. Three versions of the sealing mechanism are available to form a 2-punch key joint, 3-punch key joint or a 4-punch key joint, with one reverse locking key.

 **SIGNODE®**

3610 West Lake Avenue  
Glenview, Illinois 60025